


- NOTA POSTE FOURNI AVEC UNE POCHETTE CONTENANT:
- 2 BOUCHONS D'OBSTRUCTION
  - 1 ENTREES DE CABLE TYPE ESJ16C12M14
  - 1 FOUR CABLE Ø12 A 14 MAXI
  - 1 ENTREES DE CABLE TYPE ESJ11C8M10
  - 1 FOUR CABLE Ø8 A 10 MAXI
  - 1 BUCHON REDUCTEUR PE16/PE11

- NOTA STATION IS DELIVERED WITH BAG WHO INCLUDES:
- 2 SEALING CAPS
  - 1 CABLE ENTRY TYPE ESJ16C12M14
  - 1 FOR Ø12/14 MAX CABLE
  - 1 CABLE ENTRY TYPE ESJ11C8M10 FOR Ø8/10 MAX CABLE
  - 1 CABLE ENTRY REDUCER PE16/PE11

RACCORDEMENT  
(sur carte mere WK234U2G)  
WIRING  
(on card WK234U2G)



**DESCRIPTION:**  
POSTE SECONDAIRE 1 DIRECTION TYPE MURAL ETANCHE (INDICE DE PROTECTION IP66), COMPOSE D'UNE BOITE ET D'UN COUVERCLE EN METAL LEGER, PROTEGER PAR PEINTURE EPIKOTE. LA FERMETURE DU COUVERCLE, PIVOTANT SUR CHARNIERES A 180° ET DECONDABLE, SEFFECTUE SUR JOINT D'ETANCHEITE PAR 4 VIS IMPERDABLE SIX PANS CREUX OU SPECIALES (INVOLABLE EN OPTION).

- (A) HAUT PARLEUR ETANCHE SW/50 OHMS CE124V11
- (B) CARTE MERE UNIVERSAL2 WK234U2G
- (C) CARTE 1 BOUTON WK024CBT
- (D) MICROPHONE ELECTRET CE515V2
- (E) ENTREES DE CABLE ( VOIR NOTA ) GM208A10

POIDS: 4.2 Kg  
REFERENCE: TLH376E1G SCHEMA DE PRINCIPE: SP024CBT + SP234U2G

**DESCRIPTION:**  
1 WAY WEATHERPROOF WALL MOUNTING SUBSTATION TYPE (IP66) COMPRISING A LIGHT ALLOY BACK CASE AND FRONT COVER PROTECTED BY EPIKOTE PAINT. THE FRONT COVER WHICH PIVOTS AT UP TO 180° AND IS REMOVABLE, CLOSES ON TO A WEATHERPROOF SEAL VIA 4 CAPTIVE STAINLESS STEEL SCREWS.

- (A) SW/50 OHMS LOUDSPEAKER CE124V11
- (B) MOTHER BOARD UNIVERSAL2 WK234U2G
- (C) 1 BUTTON CARD WITH LED WK024CBT
- (D) ELECTRET MICROPHONE CE515V2
- (E) CABLE ENTRIES ( SEE NOTA ) GM208A10

WEIGHT: 4.2 Kg  
REFERENCE: TLH376E1G CIRCUIT DIAGRAM: SP024CBT + SP234U2G

CONSTRUCTEUR Manufacturer		<b>SYSCOM</b>		34/36 R. Roger SALENGRO F94134 FONTENAY/BOIS	
MATIERE:		EXECUTION:		Echelle: 1/3	
INTERPHONE UNIVERSAL 2		POSTE SECONDAIRE ETANCHE IP66 1 DIRECTION		1/3 01 376E-ENC	
1 WAY WEATHERPROOF SUBSTATION		WALL MOUNTED TYPE - IP66		TLH9376E1G	
29/3/99	A	EMISSION/Initial issue	VERIFIABLE	APPROUVE	FOLIO
DATES	REV	MODIFICATIONS	VERIFIABLE	APPROUVE	
Index	Revis	Revisions	Revis	Revis	